

Enjoy **your results**

30 YEARS ROHDE 

The kiln that comes to meet you.



It needs the same space as a frontloader but has the advantages of a truck kiln.

- **Drawer bottom** – the new way of kiln loading. **New: drawer without table frame.**
- **Ergonomically designed** – easier to load from three sides, **kind to your back.**
- **Economic** – faster and more compact loading, **better all round view.**
- **Energy efficient** – due to high-quality, **3-layer insulation with in-frame ventilation.**

Technical Data of the new Ergo Load Series ELS-S up to 1320°C

Model	Interior dimensions			Exterior dimensions			Working height	Output	Current	Plug	Weight
	(mm)			(mm)							
Volume	w	d	h	W	D	H	mm	kW	(3 Phase) A		net kg
ELS 200 S	460	640	680	800	1110	1730	700	13,2	20	CEE 32 A	540
ELS 330 S	580	710	800	920	1190	1740	700	22,0	32	CEE 32 A	640
ELS 480 S	630	770	995	990	1250	1760	550	32,0	47	CEE 63 A	870
ELS 750 S	710	1020	1030	1030	1050	1770	550	50,0	73	–	1125
ELS 1000 S	910	1005	1145	1250	1490	1890	550	70,0	100	–	1250

For more details about the ELS II please contact your ROHDE dealer or us:
Helmut Rohde GmbH · Ried 9 · D-83134 Prutting · info@rohde-online.net

www.rohde-online.net