

ROHDE Frontloading Kiln KE-B Series

for temperatures up to 1300°C



The Chamber-Kiln KE-B Series is a solid kiln series for applications in professional workshops, schools and hobby pottery.

In this kiln we have combined state-of-the-art technology with the high-quality workmanship of tried and tested materials.

A special feature of this kiln series is the complete back ventilation of the kiln body, which actively prevents corrosion. As a result the outside temperature of the kiln is extremely low.

A further feature is the mortar-free construction of the kiln ceiling. This prevents the goods from being damaged by material dropping from above.

Special features of the KE-B Series:

- heating from 3 sides recessed in grooved brick walls
- Insulation consists of 2 layers, lightweight firebricks in firing chamber
- Steel frame with all-round back ventilation for low outer temperatures and active corrosion protection
- Upper door frame made of stainless steel
- Peep-hole in door
- Air-supply and exhaust air hole
- Fully automated kiln controller
- Safety switch according to DIN, VDE standards
- Wiring prepared for either 1-phase or 3-phase operation
- 36 months guarantee
- Unit construction

Model	Volume		Interior Dimens. (mm)			External Dimens. (mm)			Output kW	Supply		Bats mm	Weight kg
	litre	ft ³	w	d	h	W	D	H		A 3Ph	A 1Ph		
KE105B	105	3,3	450	410	608	760	860	1600	7	10	30	370x340	260
KE130B	130	4,6	450	450	684	760	900	1600	8	12	35	420x400	330
KE170B	172	6,0	450	530	760	760	980	1600	9	13	39	440x400	360
KE210B	207	7,3	450	640	760	760	1100	1600	11	16	48	560x400	390

Please contact us for more information!

Helmut Rohde GmbH · Ried 9 · D-83134 Prutting · e-Mail: info@rohde-online.net · www.rohde-online.net